UOTEK AC Power three-phase surge protector



UT-M4-40C



1. Continuous operating voltage: 380VAC

2. Maximum continuous operating voltage: 385VAC

3. Through-current capacity (In): 20KA

4. Max. through-current capacity (Imax): 40kA

5. Maximum discharge current In: 10KA

6. Protection level (Up at In): ≤1500V

7. Access wire area: 6 mm²

8. Response time ta: <25ns





1.Overview

UT-M4-40C AC power surge three-phase protector is mainly used for C-level protection of power distribution system, used to protect electrical and electronic equipment from lightning electromagnetic pulse induced voltage, operating transient and resonance (<100µs) overvoltage, widely used in communication equipment, electrical, electrical appliances, power equipment, security monitoring, transportation, industrial control, aviation and other fields of power protection. This series of products has the characteristics of extremely fast response time, built-in thermal protection, low residual voltage, timely tripping, etc., and the flame retardant level reaches V-O level, which can prevent fire to the greatest extent and play a role in safety protection.


2.Specification

2.opecimenton		
Item	UT-M4-40C	
Product Name	UOTEK AC Power surge three-phase protector	
Hardware Specification		
Continuous operating voltage	380VAC	
Maximum continuous operating voltage	385VAC	
Through-current capacity (In)	20KA	
Max. through-current capacity (Imax)	40kA	
Maximum discharge current In	10KA	
Protection level (Up at In)	≤1500V	
Access wire area	6 mm ²	

Vour Reliable Partner in Industrial IoT

Response time(ta)	<25ns
Telecommunication definition (optional)	NC-COM is normally closed, COM is common point, NO-COMisnormally open
Failure indication	green: normal, red: failure
Dimension	90*72*65mm
Protection level	IP20
Front fuse	30AgL/gG
Protection mode	L1 L2 L3 N /PE L1 L2 L3/N N/PE
Flame retardant grade	V0/red
Installation mode	35 mm rail mounting
Operating environment	temperature -40 $^{\sim}$ 85°C, relative humidity \leq 95% (25 °C), height \leq 3km

3.Dimension



4. Appearance



5. Ordering

Model	Description
UT-M4-40C	UOTEK AC Power three-phase surge protector