

# 100M Network Fiber Optic Transceiver



## UT-2604-220

4-Port 100M Network Fiber Optic Transceiver



- Adopt high quality optoelectronic integrated modules to provide good optical and electrical characteristics, ensure reliable data transmission and long lifecycle
- Supports full-duplex and half-duplex, auto negotiation
- Auto-10/100Mbps
- Fully automatic recognition of network interface
- Plug and play for easy access
- Operating temperature: -40~85°C
- Input voltage:110/220VAC(88~264VAC)/50-60Hz or 110/220VDC (88~264VDC) ,The device supports dual power redundant input



## OVERVIEW

UT-2604-220 series is a 100M network fiber optic transceiver, providing four 10/100Base-T(X) Ethernet ports and one 100Base-FX port; used for Ethernet port and fiber optic cable data communication, it is suitable for the scenarios of intelligent community or FTTD(fiber to the desk).The series of products support -40~ 85°C work and good EMC performance to ensure normal operation in harsh environments, the series will greatly extend the distance of network transmission, can easily achieve the interconnection between the main board server, repeater, hub, terminal and terminal, for video surveillance, finance, education and other industries to form a network to provide cost-effective, safe and reliable solutions.

## SPECIFICATION

### Protocol Standards

IEEE 802.3, IEEE 802.3u, IEEE 802.3x

### Interfaces

Fiber interfaces: 1\*100Base-FX (SC/FC/ST)

RJ45 interface: 4\*10/100Base-TX, auto MDI/MDI-X

### Transmission Distance

Cat.5e: 100m

Patch cord

Single-mode: 1310nm 20/40/60Km

1550nm 80/100/120Km

Multi-mode: 1310nm 2Km

### Switching Performance

Forwarding Rate: 148,810pps

Transmission mode: store and forward

MAC address size: 1K

Cache size: 0.5Mb

Backplane bandwidth: 1.2G

### Power Requirement

Voltage input: 110/220VAC(88~264VAC)/50-60Hz or 110/220VDC (88~264VDC)

Power consumption: the rated power of the device is 10W

Terminal block: One pluggable 6-pin terminal block

Index parameter	100Base-X			
	Multi-	Singal-mode		
Dual fiber transmitting and	1310	1310	1310	1550
Send signal fiber (T type)	Send the	1310	1310	1490
	Receive the	1550	1550	1550
Receive signal fiber (R type)	Send the	1550	1550	1550
	Receive the	1310	1310	1490
Transmission distance Km	2	20	40	80
Transmit power dBm	-15~-8	-15~-8	-5~0	-5~0
Receive sensitivity dBm(≤)	-32	-34	-34	-34
Optical saturation dBm	-3	-3	-3	-3
Optical loss dBm/Km	0.5	0.5	0.3	0.25
Electrical port data transmission	10/100Mbps			

For example: UT-2604RSM-SC-40-220, "R" is receiving single fiber, "SM" is single mode, "SC" fiber interface type is SC head, "40" transmission km for 40km

Fiber core diameter:

Multi-mode: 50/125, 62.5/125

Single-mode: 8.3/125, 9/125, 10/125.

**Mechanical Characteristics**

IP protection level: IP40

Installation: DIN-Rail/Wall Mounted

**Operating Environment**

Operating temperature: -40 ~ 85°C

Storage temperature: -40 ~ 85°C

Relative humidity: 0 ~ 95%

**Mechanical Dimension**

Dimension (W x H x D): 150mm x 100mm x 47.6mm

Packaging dimension: 250mm x 205mm x 55mm

Weight: 650g

**Industrial Standards**

EMI:

FCC Part 15 Subpart B classA, EN55022 class A

EMS:

IEC(EN)61000-4-2(ESD)

IEC(EN)61000-4-3(RS)


IEC(EN)61000-4-4(EFT)

IEC(EN)61000-4-5(Surge)

IEC(EN)61000-4-6(CS)

IEC(EN)61000-4-8

IEC 60068-2-27(Shock)



## ORDERING

Model	Interface		Optical port description
	10/100Base-TX	100Base-FX	
UT-2604SM-SC-220	4	1	Single-mode dual-fiber SC
UT-2604SM-ST-220	4	1	Single-mode dual-fiber ST
UT-2604SM-FC-220	4	1	Single-mode dual-fiber FC
UT-2604MM-SC-220	4	1	Multi-mode dual-Fiber SC
UT-2604MM-ST-220	4	1	Multi-mode dual-Fiber ST
UT-2604MM-FC-220	4	1	Multi-mode dual-Fiber FC
UT-2604P-220	4	1	SFP slot

**Remarks:**

- Optional single fiber transceiver, if the product in the "SM" or "MM" before the addition of "R" (receiving end) or "T "(transmitter), such as UT-2604RSM-SC-220 means single mode single fiber, SC connector, 20KM.
- The suffix "220" of the product means 110/220VAC/DC (88~264VAC/DC) input for power supply.